

TimeMate SPBL65

World's Smallest Combined Fingerprint & Card Reader with Access Control.



The world's smallest IP-based fingerprint terminal with time attendance and access control capability. With rugged IP65 rated waterproof structure, it offers extra durability and it's perfect for outdoor installation. From simple door control to complex networked environment, It supports full functionality of time attendance and access control. All features comes in an elegantly designed, slick and slim device.









Powerful 400MHz DSP

Powered by 400MHz DSP, delivers fast matching speed, rapid response and exceptionally low error rate. This powerful processor is capable of handling fast and accurate fingerprint matching process, and ensures uninterrupted device operation.

IP65-rated Waterproof Structure

Body structure has been comprehensively sealed against invasive moisture, dust and liquid. Featuring superb IP65-rated protection, its meticulous sealing, combined with extra protective engineering, ensures faultless operation under outdoor installation. Also features illuminated keypads, LCD back light and LED indicator for excellent visibility in harsh conditions



Features

Rugged structure for outdoor installation and extra durability

IP65 rated waterproof and weatherproof structure

Fast and accurate fingerprint identification

Award winning fingerprint algorithm (No.1 in FVC2004 and FVC2006) 1: 2,000 fingerprint identification in 1 second

Easy installation and connectivity

Network interface by TCP/IP or RS485 Wiegand input/output configurable up to 64 bits Internal relay for direct lock interface (standalone control mode)

Easy operation and management

Built-in keypad and RF card reader for multi-modal userauthentication (Fingerprint, PIN, card)
Easy-to-use PC software for access control and time attendance Template on card to store fingerprint data on a smart card

Slim and elegant design

World's smallest fingerprint terminal for time attendance and access control Slick and Slim design for narrow spaces Graphic LCD, Multi color LED and multi-tone buzzer for intuitive user interface

Full access control features

128 access groups and time schedules Anti-passback door zones supporting 64 readers Tamper switch and duress finger option

Integrated with TimeMate Software

Time Attendance management solution available with Intelliob TimeMate software.

Device Configuration

CPU 400MHz DSP Memory 8MB flash + 16MB RAM

Fingerprint Sensor 500 dpi optical sensor Identification Speed 2,000 matches in 1 second

Fingerprint Capacity 5,000 fingerprints (10,000 templates)

Log Capacity 50,000 events

RF Card Mifare (13.56 MHz)

Authentication Finger / PIN / Card

Network Interface TCP/IP, RS485

Wiegand 1 channel (input/output switchable)

TTL I/O 2 inputs for exit switch and door sensor

Internal Relay Deadbolt, EM lock, door strike, automatic door

Ingress Protection Rate IP65 class

LCD 128 x 64 pixel, black & white

Keypad 3 x 4 keypad, 3 navigation keys Sound and Interface Multi-color LED and multi-tone buzzer

Operating Voltage 12VDC

Size 60 x 185 x 40 mm (W x H x D)

Integrated with TimeMate Software by

Intelliob Technologies Pvt Ltd. C-110 Gambhir Estate, Off Aarey Road, Goregoan East, Mumbai, India.

Phone: 022 28791193 / 022 28768198

Web: www.intelliob.com
Web: www.timemate.in